

Flat Bed Equipment Trailers

14,000 lbs.

All units include:

- Accu-lube Straight Axles
- (2) Brakes
- Slipper Springs
- Break away box
- Treated Pine Flooring
- Stake Pockets
- 2' Dovetail
- 4' Ramps
- 2 5/16" Coupler
- "A" Frame Jack
- Spare Mount
- 16" 8 Lug Radial



8" Channel Main Frame

Model	GVWR	S.W.	T/W Size	Pay Load
8214EQ-14K	14,000 lbs.	2200 lbs.	8 Lug 16"	12,000 lbs.
8216EQ-14K	14,000 lbs.	2400 lbs.	8 Lug 16"	12,000 lbs.
8218EQ-14K	14,000 lbs.	2600 lbs.	8 Lug 16"	12,000 lbs.
8220EQ-14K	14,000 lbs.	2900 lbs.	8 Lug 16"	12,000 lbs.

Options:

- | |
|----------------------------------|
| Adjustable 2 5/16" Hitch |
| Adjustable Pintle Ring |
| 12" Landscape Side Railing |
| Full Landscape Spring Assist |
| Gate - Heavy Duty Expanded Metal |
| Toolbox Mounted in Tounge |



** Trailer Design And Parts Subject To Change Without Notice

Carolina Trailer

400 Corporate Blvd Rock Hill, SC 29730
 Phone: (803) 329-3074 Fax: (803) 329-0443

e-mail: sales@CarolinaTrailerOnline.com
 www.CarolinaTrailerOnline.com