

Gooseneck Equipment Deckover

All units include:

- Accu-lube Brake Axles
- Adj. 2 5/16" Gooseneck Hitch
- 96" Bed
- Stake Pockets
- Rub Rail
- Treated Pine Floor
- Break Away Box
- Duel 10,000 lb. Spring Loaded Jack
 (1) 10K (2) 12K & 14K (except 10K)
- 5' Self Cleaning Dove Tail
- 5' Ramps
- Recessed Rubber Lighting



Model	Size	GVWR	S.W.	T/W Size	Pay Load
820GND0	8' x 20'	10,000 lbs.	2,900 lbs.	6 Lug 15"	8,000 lbs.
820GND0	8' x 20'	12,000 lbs.	3,200 lbs.	8 Lug 16"	10,000 lbs.
820GND0	8' x 20'	14,000 lbs.	3,600 lbs..	8 Lug 16"	12,000 lbs.
825GND0	8' x 25'	10,000 lbs.	3,500 lbs.	6 Lug 15"	8,000 lbs.
825GND0	8' x 25'	12,000 lbs.	3,900 lbs.	8 Lug 16"	10,000 lbs.
825GND0	8' x 25'	14,000 lbs.	4,000 lbs.	8 Lug 16"	12,000 lbs.
830GND0	8' x 30'	14,000 lbs.	4,500 lbs.	8 Lug 16"	12,000 lbs.

10K = 8" Channel Main Rail

12K & 14K = 12" I Beam Frame



Options:
Flat Deck on Top of Gooseneck
Decked w/ Railing on Top of Gooseneck
Lay Flat Spring Assist Ramps
Pop Up Dove Tail
No Dove Tail and No Ramps
1/8" Treadplate Floor IPO Wood

** Trailer Design And Parts Subject To Change Without Notice

Carolina Trailer

400 Corporate Blvd Rock Hill, SC 29730
 Phone: (803) 329-3074 Fax: (803) 329-0443

e-mail: sales@CarolinaTrailerOnline.com
 www.CarolinaTrailerOnline.com